

Website: www.naili.ltd Email: jim@naili.ltd WhatsApp: +86 180 2894 1262


## **Hydraulic Conveyor – Medium – 7000 mm Length - Parameters**

Parameter Name	Specification	
General parameters		
Minimum Speed	0.3 m/min	
Maximum Speed	30 m/min	
Overall length	7000 mm	
Load Capacity	80 kg/m	
Equi	pment parameters	
Overall Machine Length	7000 mm	
Slope Section Length	4000 mm	
Lower Platform Length	1100 mm	
Support Frame	2000 mm / 3500 mm	
Load Capacity	80 kg/m	
Speed	30 m/min	
Width	600 mm / 800 mm	
Roller Diameter	Drive: 130 mm Idle: 45 mm	
Axis Core Diameter	Drive: 35 mm Idle: 15 mm	
Conveyor Body	Thickness: ≥ 3.0 mm Material: Q345 Process: Surface electrostatic spray treatment	
Equipment Frame	Thickness: ≥ 3.0 mm  Material: Q235B14#  Process: Surface electrostatic spray treatment	

Parameter Name	Specification	
Accessories parameters		
Belt Operation	750 W 50 Hz 220/380 V	
Inverter Model	AS2-107 1HP 1.5 kW 220/380 V	
Hydraulic Pump	YS90L-4 220/380V	
Hydraulic Cylinder	Outer diameter: 60 mm Shaft diameter: 28 mm Travel: 700 mm Thrust: 5 tons	
Oil Pipe Material	SAE Standard Double-layer Fiber Hydraulic Pipe 53 MPa Pressure Resistance	
Belt Material	PVC 5.0 mm Black Grass Pattern Anti- Slip Belt (Wear-resistant)	
Drive Mode	Gear Engagement (#60 Chai)	
Electrical Control Box	Compliant with relevant national standards	
Control Panel	Forward/Reverse Lift/Lower Emergency Stop	
Electrical Components	Leakage Protection, AC Contactor (Domestic Brand)	
Heavy-Duty Casters	Wheel width 50mm, Height 200mm, Full Brake, Designed for Load	
Warranty		
Machine Warranty	1 Year	

Compatible Products for Large Hydraulic Conveyor Extension		
Product Name	Number of Sections (Max)	Maximum Extended Length
Gravity Skate Wheel Conveyor	6 sections	12.6 meters
38mm Gravity Roller Conveyor	6 sections	10.2 meters
50mm Gravity Roller Conveyor	4 sections	6 meters
Multi-wedge Belt Driven Roller Conveyor (2 Meters)	5 sections	10 meters
O-shaped Belt Driven Roller Conveyor	5 sections	7.5 meters
Rubber Roller Conveyor	5 sections	5.5 meters





Warranty Policy	Our Warranty Policy: One year warranty for the conveyor main body and motor. Six months warranty for the driven belt. If the issue with the spare parts is not caused by human damage, we will provide replacement parts free of charge. However, as this involves international shipping, we kindly ask the customer to cover the freight cost. For any damage caused by human error within one year, or for issues that arise outside the warranty period, both the cost of the parts and the shipping will need to be covered by the customer.
-----------------	---