



Website: www.naili.ltd
Email: jim@naili.ltd
WhatsApp: +86 180 2894 1262

Hydraulic Conveyor – Micro – 3700 mm Length - Parameters

Parameter Name	Specification	Parameter Name	Specification
General parameters		Accessories parameters	
Minimum Speed	0.3 m/min	Belt Operation	750 W 50 Hz 220/380 V
Maximum Speed	30 m/min	Inverter Model	0.75 kW 220/380 V
Overall length	3700 mm	Hydraulic Pump	YS90L-4 50 Hz 2.2 kW 220/380V
Load Capacity	50 kg/m	Hydraulic Cylinder	Outer diameter: 60 mm Shaft diameter: 28 mm Voltage: 24/48/220/380 V
Equipment parameters		Belt Material	PVC 5.0 mm Black Grass Pattern Anti-Slip Belt (Wear-resistant)
Overall Machine Length	3700 mm	Drive Mode	Gear Engagement
Upper Platform Length	800 mm	Electrical Control Box	Compliant with relevant national standards
Climbing Platform Length	2000 mm	Control Panel	Forward/Reverse Lift/Lower Emergency Stop
Lower Platform Length	1000 mm	Electrical Components	Leakage Protection, AC Contactor (Domestic Brand)
Speed	30 m/min	Heavy-Duty Casters	Wheel width 50mm, Height 200mm, Full Brake, Designed for Load
Load Capacity	50 kg/m	Warranty	
Width	600/800 mm	Machine Warranty	1 Year
Roller	Diameter: 89 mm Process: Zinc-plated surface treatment	Warranty Policy	
Axis Core	Diameter: 25 mm Process: Zinc-plated surface treatment		
Conveyor Body	Thickness: ≥ 3.0 mm Material: Q345 Process: Baked Paint Coating		
Equipment Frame	Thickness: ≥ 2.0 mm Material: Steel Process: Baked Paint Coating		

